## SPECIFICATION SHEET

## PRODUCT # BQ512-AB BBQ Mini Lighthouse

Housing: Solid brass construction and copper

construction. Three "O" Ring rubber seal on post for moisture protection. Ceramic white paint under shade for

maximum photometrice.

Frosted lens reduces glare and gives

softer illumination.

High Temperature ceramic socket Socket:

with nickel contacts, Stainless Steel spring. Rubber bug plug in lead wires exit stem to protect moisture and

insects entering the fixture.

MR-16 Lamp type 12V Max wattage

50W.

Lens:

Lamp:

Mounting: In-ground ABS Stake.

Wiring:

**Electrical Notes:** A remote 12V transformer required,

> may be ordered to Elram, Inc. separately. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are

3' #18/2 Direct bury landscape lighting

hub-ready leads for quick installation.

wire with UL listed, Pre-stripped

9V-17V.

Hardware: Hexagonal crew fix to part.

Warranty: Limited lifetime Warranty.

Gasket: A thick rubber gasket.

| MOUNT        | LIGHT ENGINE                                   | SERIES                 | COLOR TEMP  | FINISH            | LUMEN   | BEAM °              |
|--------------|--|------------------------|---|-------------------|---|---------------------|
| BQ           |  | 512                    |   |                   |   |                     |
| BQ BBQ Light | blank No Lamp<br>L LED Lamp<br>D Not Available | BBQ Mini<br>Lighthouse | <b>WW</b> 2700K<br><b>3K</b> 3000K<br><b>4K</b> 4000K | AB Antique Bronze | <b>05</b> 500lm<br><b>06</b> 650lm<br><b>07</b> 550lm | SP 20°<br>blank 36° |

