

## SPECIFICATION SHEET

### PRODUCT # GW202-SS Grilled In-Ground

**Housing:** Die-cast aluminum knuckle and adjustable thumb screw. Easy adjustable for vertical tilt and horizontal rotation.

**Lens:** Heat resistant Convex Glass Lens is fully sealed with silicon sealant reduces water build-up and puddle on the lens. Flat Tempered Glass.

**Socket:** High Temperature ceramic socket with nickel contacts, Stainless Steel spring.

**Lamp:** MR-16 Lamp type, 12V Max wattage 50W.

**Gasket:** A thick rubber gasket.

**Wiring:** 3' #18/2 Direct bury landscape lighting wire with UL listed, Pre-stripped hub-ready leads for quick installation.

**Mounting:** In-ground ABS Stake or Surface/Tree Mounting.

**Electrical Notes:** A remote 12V transformer required, may be ordered to Elram, Inc. separately. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are 9V-17V.

**Hardware:** Hexagonal crew fix to part.

**Warranty:** Limited lifetime Warranty.

MOUNT	LIGHT ENGINE	SERIES	COLOR TEMP	FINISH	LUMEN	BEAM °
<b>GW</b>		<b>202</b>				
<b>GW -</b>	<b>blank</b> No Lamp <b>L</b> LED Lamp <b>D</b> Not Available	Grilled In-Ground	<b>WW</b> 2700K <b>3K</b> 3000K <b>4K</b> 4000K <b>5K</b> 5000K	<b>SS</b> Stainless steel	<b>05</b> 500lm <b>06</b> 650lm <b>07</b> 550lm <b>10</b> 750lm	<b>SP</b> 20° <b>blank</b> 36°

