

SPECIFICATION SHEET

PRODUCT # PR5062-AB Double Mini Pointer

Housing: Solid brass construction. Three "O" Ring rubber seal on post for moisture protection. Ceramic white paint under shade for maximum photometric.

Lens: Frosted lens reduces glare and gives softer illumination.

Socket: High Temperature ceramic socket with nickel contacts, Stainless Steel spring. Rubber bug plug in lead wires exit stem to protect moisture and insects entering the fixture.

Lamp: MR-8 Lamp type, 12V Max wattage 20W.

Gasket: A thick rubber gasket.

Wiring: 3' #18/2 Direct bury landscape lighting wire with UL listed, Pre-stripped hub-ready leads for quick installation.

Mounting: In-ground ABS Stake.

Electrical Notes: A remote 12V transformer required, may be ordered to Elram, Inc. separately. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are 9V-17V.

Hardware: Hexagonal crew fix to part.

Warranty: Limited lifetime Warranty.

MOUNT	LIGHT ENGINE		SERIES	COLOR TEMP	FINISH	LUMEN	BEAM °
PR			5062				
PR - Path Light	blank	No Lamp	Double Mini Pointer	WW 2700K	AB Antique Bronze	05 500lm	SP 20°
	L	LED Lamp		3K 3000K		06 650lm	
	D	Not Available		4K 4000K		07 550lm	

