## **SPECIFICATION SHEET**

## **PRODUCT # PR5141-AB Spaceship**

Housing:	Solid brass construction. Three "O" Ring rubber seal on post for moisture protection. Ceramic white paint under shade for maximum photometrice.	Wiring:	3' #18/2 Direct bury landscape lighting wire with UL listed, Pre-stripped hub-ready leads for quick installation.	
		Mounting:	In-ground ABS Stake.	
Lens:	Frosted lens reduces glare and gives softer illumination.	Electrical Notes:	A remote 12V transformer required, may be ordered to Elram, Inc. separately. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are 9V-17V.	
Socket:	High Temperature ceramic socket with nickel contacts, Stainless Steel spring. Rubber bug plug in lead wires exit stem to protect moisture and insects entering the fixture.			
Lamp:	MR-16 Lamp type, 12V Max wattage 50W.	Hardware:	Hexagonal crew fix to part.	
		Warranty:	Limited lifetime Warranty.	
Gasket:	A thick rubber gasket.	,	,	

MOUNT	LIGHT ENGINE	SERIES	COLOR TEMP	FINISH	LUMEN	BEAM °
PR		5141				
PR - Path Light	blank No Lamp L LED Lamp D Not Available	Spaceship	WW 2700K 3K 3000K 4K 4000K	<b>AB</b> Antique Bronze	05 500lm 06 650lm 07 550lm	SP 20° blank 36°



