

SPECIFICATION SHEET

PRODUCT # PR5751-AB Mini Oval

Housing: Solid brass construction. Three "O" Ring rubber seal on post for moisture protection. Ceramic white paint under shade for maximum photometric.

Lens: Frosted lens reduces glare and gives softer illumination.

Socket: High Temperature ceramic socket with nickel contacts, Stainless Steel spring. Rubber bug plug in lead wires exit stem to protect moisture and insects entering the fixture.

Lamp: G4 Lamp type, 12V Max wattage 35W.

Gasket: A thick rubber gasket.

Wiring: 3' #18/2 Direct bury landscape lighting wire with UL listed, Pre-stripped hub-ready leads for quick installation.

Mounting: In-ground ABS Stake.

Electrical Notes: A remote 12V transformer required, may be ordered to Elram, Inc. separately. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are 9V-17V.

Hardware: Hexagonal crew fix to part.

Warranty: Limited lifetime Warranty.

MOUNT	LIGHT ENGINE		SERIES	COLOR TEMP		FINISH	LUMEN	BEAM °	
PR			5751						
PR - Path Light	blank	No Lamp	Mini Oval	WW	2700K	AB Antique Bronze	05	500lm	SP 20°
	L	LED Lamp		3K	3000K		06	650lm	blank 36°
	D	Not Available		4K	4000K		07	550lm	

