

## SPECIFICATION SHEET

### PRODUCT # PR808-AB Tulip

**Housing:** Solid brass construction and copper construction. Three "O" Ring rubber seal on post for moisture protection. Ceramic white paint under shade for maximum photometric.

**Lens:** Frosted lens reduces glare and gives softer illumination.

**Socket:** High Temperature ceramic socket with nickel contacts, Stainless Steel spring. Rubber bug plug in lead wires exit stem to protect moisture and insects entering the fixture.

**Lamp:** G4 Lamp type, 12V Max wattage 20W.

**Gasket:** A thick rubber gasket.

**Wiring:** 3' #18/2 Direct bury landscape lighting wire with UL listed, Pre-stripped hub-ready leads for quick installation.

**Mounting:** In-ground ABS Stake.

**Electrical Notes:** A remote 12V transformer required, may be ordered to Elram, Inc. separately. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are 9V-17V.

**Hardware:** Hexagonal crew fix to part.

**Warranty:** Limited lifetime Warranty.

MOUNT	LIGHT ENGINE		SERIES	COLOR TEMP	FINISH	LUMEN	BEAM °
<b>PR</b>			<b>808</b>				
<b>PR - Path Light</b>	<b>blank</b>	No Lamp	Tulip	<b>WW</b> 2700K	<b>AB</b> Antique Bronze	<b>05</b> 500lm	<b>SP</b> 20°
	<b>L</b>	LED Lamp		<b>3K</b> 3000K		<b>06</b> 650lm	
	<b>D</b>	Not Available		<b>4K</b> 4000K		<b>07</b> 550lm	

