

## SPECIFICATION SHEET

### PRODUCT # SL341-AB Step Composite

**Housing:** Crafted from cast brass and PBT injection molded housing.

**Wiring:** 3' #18/2 Direct bury landscape lighting wire with UL listed, Pre-stripped hub-ready leads for quick installation.

**Lens:** Lens flush with the fixture so water cannot puddle. Frosted lens reduces glare and gives softer illumination.

**Mounting:** Flush Mount PBT Injection molded Housing.

**Socket:** High Temperature ceramic socket with nickel contacts.

**Electrical Notes:** A remote 12V or 24V transformer required, may be ordered to Elram, Inc. separately. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are 9V-17V. Wire Connectors required.

**Lamp:** MR-16 Lamp type, 12V Max wattage 50W.

**Hardware:** Hexagonal crew fix to part.

**Gasket:** A thick rubber gasket between cover and poly box for a water tight seal.

**Warranty:** Limited lifetime Warranty.

MOUNT	LIGHT ENGINE	SERIES	COLOR TEMP	FINISH	LUMEN	BEAM °
<b>SL</b>		<b>341</b>				
<b>SL</b> - Step Light	<b>blank</b> No Lamp <b>L</b> LED Lamp <b>D</b> Not Available	Step Composite	<b>WW</b> 2700K <b>3K</b> 3000K <b>4K</b> 4000K	<b>AB</b> Antique Bronze	<b>05</b> 500lm <b>06</b> 650lm <b>07</b> 550lm	<b>SP</b> 20° <b>blank</b> 36°

