

SPECIFICATION SHEET

PRODUCT # SL343-AB Eye Composite

Housing: Crafted from cast brass and PBT injection molded housing.

Wiring: 3' #18/2 Direct bury landscape lighting wire with UL listed, Pre-stripped hub-ready leads for quick installation.

Lens: Lens flush with the fixture so water cannot puddle. Frosted lens reduces glare and gives softer illumination.

Mounting: Flush Mount PBT Injection molded Housing.

Socket: High Temperature ceramic socket with nickel contacts.

Electrical Notes: A remote 12V or 24V transformer required, may be ordered to Elram, Inc. separately. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are 9V-17V. Wire Connectors required.

Lamp: MR-16 Lamp type, 12V Max wattage 50W.

Hardware: Hexagonal crew fix to part.

Gasket: A thick rubber gasket between cover and poly box for a water tight seal.

Warranty: Limited lifetime Warranty.

MOUNT	LIGHT ENGINE	SERIES	COLOR TEMP	FINISH	LUMEN	BEAM °
SL		343				
SL - Step Light	blank No Lamp L LED Lamp D Not Available	Eye Composite	WW 2700K 3K 3000K 4K 4000K	AB Antique Bronze	05 500lm 06 650lm 07 550lm	SP 20° blank 36°

