

## SPECIFICATION SHEET

### PRODUCT # SL344-AB Eyelid Composite

<b>Housing:</b>	Crafted from cast brass and PBT injection molded housing.	<b>Wiring:</b>	3' #18/2 Direct bury landscape lighting wire with UL listed, Pre-stripped hub-ready leads for quick installation.
<b>Lens:</b>	Lens flush with the fixture so water cannot puddle. Frosted lens reduces glare and gives softer illumination.	<b>Mounting:</b>	Flush Mount PBT Injection molded Housing.
<b>Socket:</b>	High Temperature ceramic socket with nickel contacts.	<b>Electrical Notes:</b>	A remote 12V or 24V transformer required, may be ordered to Elram, Inc. separately. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are 9V-17V. Wire Connectors required.
<b>Lamp:</b>	MR-16 Lamp type, 12V Max wattage 50W.	<b>Hardware:</b>	Hexagonal crew fix to part.
<b>Gasket:</b>	A thick rubber gasket between cover and poly box for a water tight seal.	<b>Warranty:</b>	Limited lifetime Warranty.

MOUNT	LIGHT ENGINE	SERIES	COLOR TEMP	FINISH	LUMEN	BEAM °
<b>SL</b>		<b>344</b>				
<b>SL - Step Light</b>	<b>blank</b> No Lamp <b>L</b> LED Lamp <b>D</b> Not Available	Eyelid Composite	<b>WW</b> 2700K <b>3K</b> 3000K <b>4K</b> 4000K	<b>AB</b> Antique Bronze	<b>05</b> 500lm <b>06</b> 650lm <b>07</b> 550lm	<b>SP</b> 20° <b>blank</b> 36°

