

SPECIFICATION SHEET

PRODUCT # SLD313-3K-BZ 13" Deck/Rail

Housing: Cast aluminum. Removable bar for a variety of uses.

Light Engine: Integrated LED, 0.5 watt 1 Single LED 28 lumens, 3000, and 4200 Kelvin, 120° beam spread, 8-18 volt AC operating voltage, 5W Halogen equivalent, -20°C to +60°C ambient temperature.

Wiring: 10' #18/2 Direct bury landscape lighting wire with UL listed, Pre-stripped hub-ready leads for quick installation, wire connector Sold separately. Gel filled wire nut part# AX-201 can be ordered from Oak Landscape Lighting.

Applications: Patios, gazebos, decks, benches, stairs, Retaining walls and outdoors living spaces.

Electrical Notes: A remote 12V transformer required, may be ordered to Elram, Inc. separately. Voltage ranges for LED lamps are 9V-12V. Increase Voltage above 12VAC may reduce the life of LED diodes.

Mounting: Stainless steel removable mounting bracket. Glare shielded, supplied with screws and anchor bolts.

Hardware: Stainless Steel Screws and mounting bracket design for anticorrosion.

Warranty: 10 year Limited lifetime warranty, with a rated life of 50,000 hours

MOUNT	LIGHT ENGINE	SERIES	COLOR TEMP	FINISH	LUMEN	BEAM °
SL	D	313				
SL - Step Deck/Rail	blank No Lamp L LED Lamp D LED Dedicated	13" Deck/Rail	WW 2700K 3K 3000K 4K 4000K	BZ Bronze	05 500lm 06 650lm 07 550lm	SP 20° blank 36°

