

SPECIFICATION SHEET

PRODUCT # GW301-BK In-ground W/ Sleeve

Housing: Die-cast aluminum knuckle with adjustable thumb screw. Easy adjustable for vertical tilt and horizontal rotation.

Wiring: 3' #18/2 Direct bury landscape lighting wire with UL listed, Pre-stripped hub-ready leads for quick installation.

Lens: Heat resistant Convex Glass Lens is fully sealed with silicon sealant reduces water build-up and puddle on the lens. Flat Tempered Glass.

Mounting: In-ground ABS Stake or Surface/Tree Mounting

Socket: High Temperature ceramic socket with nickel contacts, Stainless Steel spring.

Electrical Notes: A remote 12V transformer required, may be ordered to Elram, Inc. separately. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are 9V-17V.

Lamp: MR-16 Lamp type, 12V Max wattage 50W.

Hardware: Hexagonal crew fix to part.

Gasket: A thick rubber gasket.

Warranty: One (1) year warranty against housing and body defects.

MOUNT	LIGHT ENGINE	SERIES	COLOR TEMP	FINISH	LUMEN	BEAM °
GW		301				
GW -	blank No Lamp L LED Lamp D Not Available	In-Ground W/ Sleeve	WW 2700K 3K 3000K 4K 4000K 5K 5000K	BK Black	05 500lm 06 650lm 07 550lm 10 750lm	SP 20° blank 36°

