

SPECIFICATION SHEET

PRODUCT # GW330-3-SS 3-Port Mini In-Ground

- Housing:** Solid Copper for AB finish and CO finish with Knuckle and adjustable thumb screw. Easy adjustable for vertical tilt and horizontal rotation.
- Wiring:** 3' #18/2 Direct bury landscape lighting wire with UL listed, Pre-stripped hub-ready leads for quick installation.
- Lens:** Heat resistant Convex Glass Lens is fully sealed with silicon sealant reduces water build-up and puddle on the lens. Flat Tempered Glass.
- Mounting:** In-ground ABS Stake or Surface/Tree Mounting.
- Socket:** High Temperature ceramic socket with nickel contacts, Stainless Steel spring.
- Electrical Notes:** A remote 12V transformer required, may be ordered to Elram, Inc. separately. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are 9V-17V.
- Lamp:** MR-16 Lamp type, 12V Max wattage 50W.
- Hardware:** Hexagonal crew fix to part.
- Gasket:** A thick rubber gasket.
- Warranty:** Limited lifetime Warranty.

MOUNT	LIGHT ENGINE	SERIES	COLOR TEMP	FINISH	LUMEN	BEAM °
GW		330				
GW -	blank No Lamp L LED Lamp D Not Available	3-Port Mini In-Ground	WW 2700K 3K 3000K 4K 4000K 5K 5000K	SS Stainless Steel	05 500lm 06 650lm 07 550lm 10 750lm	SP 20° blank 36°

