

SPECIFICATION SHEET

PRODUCT # PR723-BK 3-Tier Pagoda

- Housing:** Die-cast aluminum construction. Three "O" Ring rubber seal on post for moisture protection. Ceramic white paint under shade for maximum photometric.
- Wiring:** 3' #18/2 Direct bury landscape lighting wire with UL listed, Pre-stripped hub-ready leads for quick installation.
- Lens:** Frosted lens reduces glare and gives softer illumination.
- Mounting:** In-ground ABS Stake.
- Socket:** High Temperature ceramic socket with nickel contacts, Stainless Steel spring. Rubber bug plug in lead wires exit stem to protect moisture and insects entering the fixture.
- Electrical Notes:** A remote 12V transformer required, may be ordered to Elram, Inc. separately. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are 9V-17V.
- Lamp:** G4 Lamp type, 12V Max wattage 20W.
- Hardware:** Hexagonal crew fix to part.
- Gasket:** A thick rubber gasket.
- Warranty:** One (1) year warranty against housing and body defects.

MOUNT	LIGHT ENGINE	SERIES	COLOR TEMP	FINISH	LUMEN	BEAM °
PR		723				
PR - Path Light	blank No Lamp L LED Lamp D Not Available	3-Tier Pagoda	WW 2700K 3K 3000K 4K 4000K	BK Black	05 500lm 06 650lm 07 550lm	SP 20° blank 36°

