

SPECIFICATION SHEET

PRODUCT # GW201-AB In-Ground

Housing: Heavy duty brass shroud. Body design provides enclosed, water resistant function to protect lamp inside.

Wiring: 3' #18/2 Direct bury landscape lighting wire with UL listed, Pre-stripped hub-ready leads for quick installation.

Lens: Heat resistant Convex Glass Lens is fully sealed with silicon sealant reduces water build-up and puddle on the lens. Flat Tempered Glass.

Mounting: Junction Box.

Socket: High Temperature ceramic socket with nickel contacts, Stainless Steel spring.

Electrical Notes: A remote 12V transformer required, may be ordered to Elram, Inc. separately. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are 9V-17V.

Lamp: MR-16 Lamp type, 12V Max wattage 50W.

Hardware: Hexagonal crew fix to part.

Gasket: A thick rubber gasket.

Warranty: Limited lifetime Warranty.

MOUNT	LIGHT ENGINE	SERIES	COLOR TEMP	FINISH	LUMEN	BEAM °
GW		201				
GW In-Ground	blank No Lamp L LED Lamp D LED Dedicated	In-Ground	WW 2700K 3K 3000K 4K 4000K 5K 5000K	AB Antique Bronze	05 500lm 06 650lm 02 250lm 04 480lm 06 660lm 09 880lm	SP 20° blank 36° 15° 30° 45° 60°

