

## SPECIFICATION SHEET

### PRODUCT # PR702-XX China Hat 1

**Housing:** Solid brass construction or copper construction. Three "O" Ring rubber seal on post for moisture protection. Ceramic white paint under shade for maximum photometric.

**Lens:** Frosted lens reduces glare and gives softer illumination.

**Socket:** High Temperature ceramic socket with nickel contacts, Stainless Steel spring. Rubber bug plug in lead wires exit stem to protect moisture and insects entering the fixture.

**Lamp:** LED G4 Lamp type, 12V Max wattage 20W.

**Gasket:** A thick rubber gasket.

**Wiring:** 3' #18/2 Direct bury landscape lighting wire with UL listed, Pre-stripped hub-ready leads for quick installation.

**Mounting:** In-ground ABS Stake.

**Electrical Notes:** A remote 12V transformer required, may be ordered to Elram, Inc. separately. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are 9V-17V.

**Hardware:** Hexagonal crew fix to part.

**Warranty:** Limited lifetime Warranty.

MOUNT	LIGHT ENGINE	SERIES	COLOR TEMP	FINISH	LUMEN	BEAM °
<b>PR</b>		<b>702</b>				
<b>PR - Path Light</b>	<b>blank</b> No Lamp <b>L</b> LED Lamp <b>D</b> Not Available	China Hat 1	<b>WW</b> 2700K <b>3K</b> 3000K <b>4K</b> 4000K	<b>AB</b> Antique Bronze <b>CO</b> Copper	<b>05</b> 500lm <b>06</b> 650lm <b>07</b> 550lm	<b>SP</b> 20° <b>blank</b> 36°



Solid Brass Antique Bronze (AB) Finish



Copper Construction (CO) Finish

