

SPECIFICATION SHEET

PRODUCT # PR818- Orchid Path Light Square

Housing: Solid brass construction. Brass Adjustable Head. Three "O" Ring rubber seal on post for moisture protection.

Lens: Frosted lens reduces glare and gives softer illumination.

Socket: High Temperature ceramic socket with nickel contacts, Stainless Steel spring. Rubber bug plug in lead wires exit stem to protect moisture and insects entering the fixture.

Lamp: G4 Lamp type, 12V Max wattage 20W.

Gasket: A thick rubber gasket.

Wiring: 3' #18/2 Direct bury landscape lighting wire with UL listed, Pre-stripped hub-ready leads for quick installation.

Mounting: In-ground ABS Stake.

Electrical Notes: A remote 12V transformer required, may be ordered to Elram, Inc. separately. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are 9V-17V.

Hardware: Hexagonal crew fix to part.

Warranty: Limited lifetime Warranty.

MOUNT	LIGHT ENGINE	SERIES	COLOR TEMP	FINISH	LUMEN	Stem size
PR		818				
PR - Path Light	blank No Lamp L LED Lamp D Not Available	Orchid Square	WW 2700K 3K 3000K 4K 4000K	AB Antique Bronze MB Midnight Black	1.5 100lm 03 200lm 04 300lm	18 18"

