Oak Landscape Lighting

CATALOG #			
PROJECT NAME		TYPE	

Product Data Sheet

- **Conductors:** Two fully annealed bare stranded copper conductors
- **Insulation/Jacket:** Premium-grade PVC -20°C to +75°C
- **Final assembly:** Insulated/Jacketed conductors duplexed in a flat construction for easy tear-down during installation

Part No:	LV 142
Description:	14/2 LOW VOLTAGE LIGHTING
Approvals:	MEETS OR EXCEEDS UL

Conductors

Stranding	14-41 STR BC
Insulation	.045 PVC MATERIAL, 75 DEG C
Conductor OD:	0.168 +/-.002

Jacket Color	BLACK
O/A Cable Dia	0.341 X 0.168 +/-.005
Nom Wte per 1K Feet	55

Jacketing Notes	BLACK STANDARD - WHITE & BROWN AVAILABLE SPECIAL ORDER ONLY
Printing	E323739 (UL) 14/2 LOW VOLTAGE LANDSCAPE LIGHTING 30V
Packaging	250' & 500' STANDARD, 1000', 2500' REELS AVAILABLE BY SPECIAL REQUEST
Electrical/Physical	30V

- Outdoor Accent Lighting
- Landscape Lighting
- Security Lighting
- Sunlight Resistant
- Direct Burial



© 2020 ELRAM, Inc. Elram, Inc. holds the right to change the design of our products at any time.