

SPECIFICATION SHEET

PRODUCT # SL350-XX

Housing: Solid Brass construction.

Lens: Frosted lens is fully sealed with silicon sealant reduce water enter. Frosted lens reduces glare and gives softer illumination.

Socket: High Temperature ceramic socket with nickel contacts, Stainless steel spring.

Lamp: MR-16 Lamp type, Max wattage 25W or G-4 Lamp type, Max wattage 25W.

Gasket: A thick rubber gasket between cover and poly box for a water tight seal.


Wiring: 3' #18/2 Direct bury landscape lighting wire with UL listed, Pre-stripped hub-ready leads for quick installation.

Mounting: Surface Mounting.

Electrical Notes: A remote 12V or 24V transformer required, may be ordered to Elram, Inc. separately. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are 9V-17V. Wire Connectors required.

Hardware: Hexagonal crew fix to part

Warranty: Limited lifetime Warranty



ORDERING INFORMATION

Sample Part Number: **SL350-AB** (Image showing Antique Bronze)

MOUNT	LIGHT ENGINE	SERIES	FINISH	VOLTAGE	LAMP
SL - Surface Step light	blank - LED G4	350 - Half Moon	56 - Antique Bronze BB - Brushed Nickel ; A -Gun Metal A6 -Mid Night Black	blank - 12V	L -

ACCESSORIES

All Oak Landscape Lighting LED lamps have a 5 year limited warranty against manufacturers defect.

When ordering LED lamp with fixture Incorporate Lumen Output, CCT, and Beam° or just Lamp # Into the part number from the lamp Chart.