SPECIFICATION SHEET

PRODUCT # GR528-xx

Housing: Die-cast aluminum Knuckle with

adjustable thumb screw. Easy adjustable

for vertical tilt and horizontal rotation.

Lens: Heat resistant Convex Glass Lens

is fully sealed with silicon sealant reduces water build-up and puddle on the lens.

Flat Tempered Glass.

Socket: High Temperature ceramic socket with

nickel contacts, Stainless Steel spring

Lamp: LED MR16 Lamp type, Max wattage 50W.

Gasket: High temperature silicone O-ring for water

tight seal.

Wiring: 3' #18/2 Direct bury landscape lighting

wire with UL listed, Pre-stripped hub-ready leads for quick installation.

Mounting: In-ground ABS Stake or Surface/Tree

Mounting.

Electrical Notes: A remote 12V transformer required,

separately. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are

may be ordered to Elram, Inc.


9V-17V.

Hardware: Hexagonal crew fix to part

Warranty: One (1) year warranty against

housing and body defects.





ORDERING INFORMATION

Sample Part Number: GR528-BK-L2000

MOUNT	LIGHT	SERIES	FINISH	LAMP	AVILABLE WATERPROOF LED MR16 LAMPS						
					LAMP #	BEAM °	ССТ	Wattage	Equivalent	Lumen	Rated Hours
	ENGINE				L1900	15°	27	4W	20W Halogen	300lm	50,000
GR - In-ground ABS Stake	blank - LED MR16	528 - Aluminum Snowdrop	BK -Black		L1901	15°	3K	4W	20W Halogen	300lm	50,000
				L2000 -	L1902	15°	4K	4W	20W Halogen	300lm	50,000
				7W LED	L1910	45°	27	4W	20W Halogen	300lm	50,000
			BZ -Bronze	MR16	L1911	45°	3K	4W	20W Halogen	300lm	50,000
				2700K	L1912	45°	4K	4W	20W Halogen	300lm	50,000
TR -			BE -Beach		L1915	60°	27	4W	20W Halogen	300lm	50,000
	t				L1916	60°	3K	4W	20W Halogen	300lm	50,000
Surface			GN -Green		L1917	60°	4K	4W	20W Halogen	300lm	50,000
Tree mount					L1990	15°	27	7W	50W Halogen	520lm	50,000
					L1991	15°	3K	7W	50W Halogen	520lm	50,000
			VG -Verde		L1992	15°	4K	7W	50W Halogen	520lm	50,000
			Green		L2000	45°	27	7W	50W Halogen	520lm	50,000
					L2001	45°	3K	7W	50W Halogen	520lm	50,000
			WH -White		L2002	45°	4K	7W	50W Halogen	520lm	50,000
					L2005	60°	27	7W	50W Halogen	520lm	50,000
					L2006	60°	3K	7W	50W Halogen	520lm	50,000
					L2007	60°	4K	7VV	50W Halogen	520lm	50,000

ACCESSORIES

In-Ground ABS Stake



Surface / Tree Mounting

