

CATALOG #

PROJECT NAME

TYPE

0.51"

| Housing: 316 | Grade Stainless Steel | Wiring: | 3' #18/2 Direct bury landscape lig |
|---|---|-------------------|---|
| | | | wire with UL listed, Pr-stripped hi ready leads for quick installation. |
| | | Mounting: | In-ground PVC Canister (Include |
| is fully sealed | Convex Glass Lens with silicon sealant uild-up and puddle on the ered Glass. | Electrical Notes: | A remote 12V transformer req may be ordered to Elram, separately. Voltage range for |
| ocket: High Tempera with nickel cor spring. | ture ceramic socket ntacts, Stainless Steel | | |
| amp: 3W CREE LED | | Hardware: | Hexagonal crew fix to part. |
| · · · · · · · · · · · · · · · · · · · | Warra | Warranty: | Limited lifetime Warranty. |
| asket: A thick rubber ga | sket. | | |

Drive-Over Rated for 2000lb

ORDERING INFORMATION

Sample Part Number: GWD133-1-3K-SS

| MOUNT | LIGHT ENGINE | SERIES | COLOR TEMP | FINISH |
|--------------------------|---------------------------------------|---|----------------------|---|
| GW - In-Ground | D - 3W LED CREE Chip (300lm) | 133-1- Mini 1-Port In-Ground | 3K - 3000K | SS- Stainless Steel MB- Black |

ACCESSORIES